




DEHUMIDIFIERS WITH EJECTOR PUMP

3PMP50

| | |
|--------------------------------|--|
| UPC Code: | 8-42149-02413-0 |
| Capacity: (pts./day) | 50 |
| Coverage: (sq. ft) | 3,000 |
| EEV Certified: | 1.85 |
| Energy Star Rated: | Yes |
| Fan Speeds: | 2 |
| Amps: | 4.7 |
| Watts: | 520 |
| Decibels: (Hi/Lo) | 55/53 |
| Bucket Capacity: (pts.) | 12.7 |
| Unit Dimensions: (WxHxD in.) | 15 ^{1/2} x 23 ^{1/4} x 11 |
| Pkg Dimensions: (WxHxD in.) | 16 ^{3/4} x 24 ^{1/4} x 12 ^{1/2} |
| Stuffing Qty: (20'/40'/40' HQ) | 303/624/832 |
| Weight: (net/gross lbs) | 37/40 |
| Min. Operating Temp: | 41°F |
| Refrigeration: | R410A |
| Outlet Configuration: |  15 AMP 115V |

Features:

- Built-in pump
- Bucket full indicator
- Water level window
- Auto shut-off/restart
- Washable filter
- Timer function
- Automatic defrost control
- Adjustable humidistat
- Easy access bucket w/handle
- Side exhaust



Direct to Drain



Ejector Pump



Electronic Controls

