





DEHUMIDIFIERS WITH  
EJECTOR PUMP

	PADP50	PADP70
<b>UPC Code:</b>	8-42149-02310-2	8-42149-02314-0
<b>Capacity:</b> (pts./day)	50	70
<b>Coverage:</b> (sq./ft.)	3,000	4,500
<b>EER Certified:</b>	1.85	1.85
<b>Energy Star Rated:</b>	Yes	Yes
<b>Fan Speeds:</b>	2	2
<b>Amps:</b>	4.7	7.5
<b>Watts:</b>	530	845
<b>Decibels:</b> (Hi/Lo)	52/53	55/54
<b>Bucket Capacity:</b> (pts.)	18	18
<b>Unit Dimensions:</b> (WxHxD in.)	15 <sup>1</sup> / <sub>4</sub> x 23 <sup>1</sup> / <sub>2</sub> x 11 <sup>1</sup> / <sub>2</sub>	15 <sup>1</sup> / <sub>4</sub> x 23 <sup>1</sup> / <sub>2</sub> x 11 <sup>1</sup> / <sub>2</sub>
<b>Pkg Dimensions:</b> (WxHxD in.)	16 <sup>1</sup> / <sub>2</sub> x 25 <sup>1</sup> / <sub>4</sub> x 14	16 <sup>1</sup> / <sub>2</sub> x 25 <sup>1</sup> / <sub>4</sub> x 14
<b>Stuffing Qty:</b> (20'/40'/40' HQ)	260/530/710	260/530/710
<b>Weight:</b> (net/gross lbs)	39/43	45/50
<b>Min. Operating Temp:</b>	41°F	41°F
<b>Refrigeration:</b>	R410A	R410A
<b>Outlet Configuration:</b>	 15 AMP 115V	 15 AMP 115V



Direct to Drain



Ejector Pump



Electronic Controls

**FEATURES**

- Built-in pump
- Bucket full indicator
- 3-way drainage
- Water level window
- Auto shut-off/restart
- Washable filter
- Timer function
- Automatic defrost control
- Adjustable humidistat
- Easy access bucket w/handle
- Top exhaust

