


DEHUMIDIFIERS

**3PAD50**



<b>UPC Code:</b>	8-42149-02410-9
<b>Capacity:</b> (pts./day)	50
<b>Coverage:</b> (sq. ft)	3,000
<b>EEV Certified:</b>	1.85
<b>Energy Star Rated:</b>	Yes
<b>Fan Speeds:</b>	2
<b>Amps:</b>	4.8
<b>Watts:</b>	535
<b>Decibels:</b>	52/50
<b>Bucket Capacity:</b> (pts.)	12.7
<b>Unit Dimensions:</b> (WxHxD in.)	15 <sup>1</sup> / <sub>2</sub> x 23 <sup>1</sup> / <sub>4</sub> x 11
<b>Pkg Dimensions:</b> (WxHxD in.)	17 x 25 <sup>1</sup> / <sub>2</sub> x 12 <sup>3</sup> / <sub>4</sub>
<b>Stuffing Qty:</b> (20'/40'/40' HQ)	294/585/812
<b>Weight:</b> (net/gross lbs)	36/39
<b>Min. Operating Temp:</b>	41°F
<b>Refrigeration:</b>	R410A
<b>Outlet Configuration:</b>	 15 AMP 115V

**FEATURES:**

- Auto shut-off/restart
- Washable filter
- Timer function
- Automatic defrost control
- Adjustable humidistat
- Easy access bucket with handle
- Bucket full indicator
- Direct-to-drain hose access
- Water level window
- Check filter light
- Comfort option: Unit controls humidity based on room temp.



Easy Access Bucket with Carrying Handle



Easy Access Washable Filter



Electronic Controls