



DEHUMIDIFIER

50 PINT




DEHUMIDIFIER FEATURES

- Direct-to-drain hose access
- Easy access bucket with handle
- Bucket full indicator
- Adjustable humidistat
- Washable filter
- Automatic defrost control
- Auto shut-off/restart
- Timer function
- Water level window
- Comfort option: Unit controls humidity based on room temperature
- Side exhaust
- Check filter light

BUCKET W/ HANDLE




WASHABLE FILTER



ELECTRONIC CONTROLS



	4PAD50
UPC CODE	8-42149-02639-4
CAPACITY (pts./Day)	50
COVERAGE (sq. ft.)	3,000
EER	2.0
ENERGY STAR RATED	Yes
FAN SPEEDS	2
AMPS	4.7
WATTS	495
DECIBELS (Hi/Lo)	55/54
BUCKET CAPACITY (pts.)	12.7
UNIT DIMENSIONS (WxHxD) (in.)	15 ^{1/2} x 23 ^{1/4} x 11
PKG. DIMENSIONS (WxHxD) (in.)	16 ^{3/4} x 25 ^{1/4} x 12 ^{1/4}
STUFFING QTY (20'/40'/40' HQ)	303/624/832
WEIGHT (Net/Gross) (lbs.)	36/39
MIN. OPERATING TEMP	41°F
REFRIGERATION	R410A
OUTLET CONFIGURATION	 15 AMP 115V



PA/SS_4PAD50/05302017

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us